Product Datasheet



10AX 250V 1Gang, 1-Way Switch

Code: SH-001

Main

Product Or Component Type	Switch
Device Application	Control
Additional Switch Application	On/off switching
Number Of Rocker	1
Switch Function	1-way
Color Tint	White, Beige, Champagne, Grey, Black
Complementary	
Technology Type	Electromechanical
Device Presentation	Complete mechanism
Actuator	Rocker
Number Of Gangs	1 gang
Material	PC (Polycarbonate): Frame Cover PC (Polycarbonate): Base PA6: Actuator Brass and copper alloy: terminals Silver alloy: contacts
Surface Finish	Glossy
Surface Treatment	Untreated
[Ue] Rated Operational Voltage	220250 V
Type Of Packing	Plastic bag
Network Type	AC
Quantity Per Set	1
Sale Per Indivisible Quantity	1
Rated Current	10 AX
Connections - Terminals	Screw terminal

Number Of Terminals	2
Rated Current	10 AX at 250 V AC, inductive 16 A at 250 V AC, resistive
[Ue] Rated Operational Voltage	250 V AC
Network Frequency	50/60 Hz
Connections - Terminals	2 screw terminals
Terminal Identifier	L L1
Tightening Torque	0.4 N.m
Clamping Connection Capacity	2.5 mm² for rigid or stranded cable(s)
Wire Stripping Length	12 mm

Environment

Standards	MS IEC 60669-1 IEC 60669-1 SS 227
Ambient Air Temperature For Operation	-540 °C
Relative Humidity	095 %
Operating Altitude	02000 m
Environmental Characteristic	Indoor use
Ip Degree Of Protection IP20	IP20

Product Dimensions

Product Width	22.5 mm
Product Height	45 mm
Product Depth	33 mm
Embedding Depth	18 mm

Packing Units

Number of units in Package 1	1 Pcs
Package 1 Width	75 mm
Package 1 Height	75 mm
Number of units in Package 2	20 Pcs
Package 2 Lenght	250 mm
Package 2 Width	88 mm
Package 2 Height	54 mm
Number of units in Package 3	200 Pcs
Package 3 Lenght	265 mm
Package 3 Width	196 mm
Package 3 Height	298 mm

Contractual warranty

	Ť
Warranty	10 years